

UNIA Cross Cultivator de adancime - Panagroteh Grup

Descriere



Echipament standard

- Ax suspensie $\varnothing$ 70-825/ $\varnothing$ 36mm
- 3 randuri de dinti CX cu dalti sudate 370mm si protectie pe arc
- Dinti CX externi cu cormana greblare
- Grapa tip A cu discuri $\varnothing$ 460mm protejate cu buloane cauciuc si sjustare adancime de lucru cu

bolt

- Tavalug Pipe Roller ø 600mm
- Ajustare hidraulica a adancimii de lucru a tavalugului
- Cadru rigid
- Adancime de lucru a dintilor CX cu dalti: 15cm
- Adancime de lucru a dintilor CX fara dalti: 30cm
- Capacitate incarcare / dinte: 550 kg
- Distanta intre dintii CX: 30cm

Echipament optional

- Set dinti CX cu brazdare inguste
- Sistem DRIVE 670 cu protap 2000cm
- Sistem DRIVE 800 cu protap 2000cm
- Protap cu ajustare multi-punct a lungimii 2.5-3.0-3.5 m (Doar CROSS DRIVE)
- Carlig remorcare ø 40m (Doar CROSS DRIVE cu protap ajustabil)
- Carlig remorcare ø 50m (Doar CROSS DRIVE cu protap ajustabil)
- Grapa de discuri tip B (Doar CROSS DRIVE)
- Ajustare hidraulica a grapei B (Doar CROSS DRIVE)
- Roti suport frontale 200/60-14.5 (Doar CROSS DRIVE)
- Versiune cu 12 Dinti CX (doar CROSS 3m)
- Versiune cu 15 Dinti CX (doar CROSS 4m)
- Placute avertizare
- Placute avertizare cu sistem iluminare
- Posibilitate montaj semanatoare ETA

Date tehnice

Date tehnice

CROSS S	3	3.5	4	3 DRIVE	3.5 DRIVE	4 DRIVE
Greutate cu tavalug Pipe ø 600mm (Kg)	1990	2380	2540	2280	2690	2860
Necesar putere (Cp)	150-180	160-190	170-200	140-170	150-180	170-200
Numar dinti	10	12	13	10	12	13
Distanta intre dinti CX (cm)	300	290	300	300	290	300
Distanta cadru-sol (cm)	850	850	850	850	850	850
Distanta cadru (cm)	750	750	750	750	750	750
Lungime (cm)	397	397	397	430	430	430

Imagini

















Video
