

# UNIA Ms/Ms-Sad Masina imprastiat ingrasaminte - Panagroteh Grup

## Descriere

---



## Echipament standard

- Inchidere mecanica a sloturilor de masurare ( Versiune MS )
- Inchidere hidraulica a sloturilor de masurare ( Versiune MS-SAD )
- Latime de lucru: 10-24 m ( Versiune MS )
- Latime de lucru: 10-18 m ( Versiune MS - SAD )
- Latime de lucru la imprastierea marginala : 2-6 m ( MS-SAD )
- Placa delimitare imprastiere ( MS )
- Placa delimitare imprastiere ( MS-SAD)
- Site buncar
- Indicator al gradului de inclinare al distribuitorului
- Tabel setare si imprastiere

- Mixer fertilizant
- Discuri imprastiere fertilizant din otel inoxidabil
- Suspensie cat. II

## **Echipament optional**

- Discuri imprastiere marginala
- Roti transport detasabile
- Inchidere hidraulica ( MS )
- Prelata buncar ( MS )
- Cardan PTO 250 Nm L. nom. 840 mm

## Date tehnice

---

### Date tehnice

| Model                      | MS 400         | MS 500         | MS-SAD 400       | MS-SAD 500       | MS-SAD 600       |
|----------------------------|----------------|----------------|------------------|------------------|------------------|
| Capacitate buncar ( dm 3 ) | 400            | 500            | 400              | 500              | 600              |
| Latime de lucru ( m ) :    | 12-24          | 12-24          | 10-18            | 10-18            | 10-18            |
| Latime transport ( m ) :   | 0.94/1,65/0,95 | 0.94/1,65/1,05 | 1,0/1,3(1,4)/1,1 | 1,0/1,3(1,4)/1,3 | 1,0/1,3(1,4)/1,5 |
| Greutate proprie ( kg ):   | 223            | 240            | 230              | 240              | 250              |
| Necesar putere ( cp ) :    | 40-50          | 50-60          | 40-50            | 50-60            | 60-70            |

## Imagini

---



