

UNIA Rook plug reversibil - Panagroteh Grup

Descriere



ROOK

Echipament standard

- Axa remorcare : Categoria III ø36 mm
- Ax reversare ø150
- Cadru 160X160 mm
- Trupite BIG LONG cu prelungire cormana
- Protectie cu bolt
- Protectie non-stop cu 7 foi de arc (Versiune S)
- Protectie hidraulica (Versiune H)

- Latime de lucru ajustabila in punct (ROOK)
- Latime de lucru ajustabila intre : 35-50 cm (ROOK VARIO)
- Roata suport laterala 320/60-12 cu amortizor (ROOK)
- Roata suport si transport spate 320/60-12 cu amortizor (ROOK VARIO)
- Disc brazdar $\varnothing 480$ mm cu protectie arc (Versiune S/H)
- Distanta intre trupite : 100 cm
- Distanta cadru-sol: 85cm si 80 pentru versiunile S/ H

Echipament optional

- Cutite brazdar
- Razuitori resturi vegetale
- Cilindru pentru ajustarea primei brazde
- Roata suport si transport spate 320/60-12 (fara VARIO)
- Roata suport si transport laterala 320/60-12 (doar 5+1)
- Intarire protectie arc cu inca 2 foi (de la 7 la 9 foi)
- Filtru pentru furtun hidraulic

Date tehnice

Date tehnice

ROOK	5+	5+1	Vario 5	Vario 6
Greutate (KG)	2120	2290	2200	2390
Necesar putere (CP)	150-220	200-330	170-240	220-350

ROOK S	5+	5+1	Vario 5	Vario 6
Greutate (KG)	2420	2700	2500	2800
Necesar putere (CP)	200-220	230-330	180-240	250-350

ROOK H	5+	5+1	Vario 5	Vario 6
Greutate (KG)	2320	2580	2400	2680
Necesar putere (CP)	160-220	230-330	180-240	250-350

Imagini



Video
